Amendments to the Claims:

This listing of claims will replace all prior versions, and listings of claims in the

application. Applicant has submitted a new complete claim set showing marked up

claims with insertions indicated by underlining and deletions indicated by strikeouts

and/or double bracketing.

1. (Currently Amended) A computer functioning as a computer-based

network switch, comprising:

a first network adapter for connecting to an external network;

a plurality of second network adapters each for forming a connection with a

network server in a private network;

a switching component for receiving network communication data from the

external network through the first network adapter and directing the received network

communication data to the second network adapters for transmission to the respective

network servers in the private network connected thereto; and

a test control component for selectively disabling the second network adapters

to create failure of physical connections between the second network adapters and the

respective network servers in the private network connected thereto, the test

controller further including a third network adapter for connecting the test control component to a server testing controller on the external network to allow the test

control component to communicate with the server testing controller.

2. Cancelled

3. (original) A computer as in claim 1, wherein the switching

component is programmed to operate on network communication data passing

Type of Response: Amendment

Application Number: 09/758,831

Attorney Docket Number: 150562.01

Filing Date: January 11, 2001

2/15

therethrough to create a communication test condition other than a connection failure condition.

- 4. (Currently Amended) A computer as in claim 3, wherein the switching component is programmed to <u>provide a preselected delay to</u> network communication data passing therethrough.
- 5. (original) A computer as in claim 3, wherein the switching component is programmed to selectively drop network communication data.
- 6. (original) A computer as in claim 3, wherein the switching component is programmed to reorder data in a communication stream passing therethrough.
- 7. (original) A computer as in claim 3, wherein the switching component is programmed to introduce errors into network communication data passing therethrough.
- 8. (original) A computer as in claim 1, wherein the switching component is programmed for monitoring flows of network communication data therethrough from the respective network servers in the private network to the external network.
- 9. (Currently Amended) A computer-readable medium having computer-executable components for controlling a plurality of network adapters in a computer

Type of Response: Amendment Application Number: 09/758,831 Attorney Docket Number: 150562.01

to create test conditions for testing network servers in a private network, the network

servers connected to the network adapters, comprising:

a switching component for receiving network communication data from an

external network and directing the received network communication data to the

network adapters for transmission to the respective network servers in the private

network connected thereto:

a test control for selectively disabling the network servers to create failure of

physical connections between the network adapters and the respective network

servers in the private network connected thereto, and configured for

sending/receiving instructions with a server testing controller over a network adapter

separate from the network adapters associated with the switching component.

10. (original) A computer-readable medium as in claim 9, wherein the

switching component includes further computer-executable instructions for operating

on network communication data passing therethrough to create a test condition other

than a connection failure condition.

11. (Currently Amended) A computer-readable medium as in claim 10,

wherein the switching component includes computer-executable instructions for

selectively buffering network communication data passing therethrough for a

preselected delay period.

12. (original) A computer-readable medium as in claim 10, wherein the

switching component includes computer-executable instructions for selectively

dropping network communication data passing therethrough.

Type of Response: Amendment

Application Number: 09/758,831

Attorney Docket Number: 150562.01

13. (original) A computer-readable medium as in claim 10, wherein the switching component includes computer-executable instructions for reordering data in a communication stream passing therethrough.

14. (original) A computer-readable medium as in claim 10, wherein the switching component includes computer-executable instructions for introducing errors into network communication data passing therethrough.

15. (original) A computer-readable medium as in claim 9, wherein the test control includes computer-executable instructions for communicating with a server testing controller to receive commands regarding testing of the network servers.

16. (original) A computer-readable medium as in claim 9, wherein the switching component includes further computer-executable instructions for monitoring flows of network communication data from the respective network servers to the external network.

17. (Currently Amended) A system for testing network servers in a private network, comprising:

a computer functioning as a computer-based network switch, including a plurality of network adapters for forming connections to the network servers, a switching component for receiving network communication data from an external network and directing the received network communication data to the network adapters for transmission to the respective network servers in the private network connected thereto, and a test control for selectively disabling the network adapters;

Type of Response: Amendment Application Number: 09/758,831 Attorney Docket Number: 150562.01

a plurality of client computers connected to the external network for communication with the network servers in the private network through the computer-based network switch;

a server testing controller connected to through the external network for coordinating testing of the network servers, including instructing the client computers to send network communication data to the network servers in the private network through the computer-based network switch, and causing the test control to selectively disable the network adapters to create failure of physical connections between the network adapters and the network servers in the private network connected thereto.

- 18. (original) A system as in claim 17, wherein the switching component is controllable to operate on network communication data passing therethrough to create a test condition other than a connection failure condition.
- 19. (Currently Amended) A system as in claim 18, wherein the switching component is controllable to selectively buffer network communication data passing therethrough to introduce a <u>preselected</u> delay.
- 20. (original) A system as in claim 18, wherein the switching component is controllable to selectively drop network communication data passing therethrough.
- 21. (original) A system as in claim 18, wherein the switching component is controllable to reorder network communication data passing therethrough.

Type of Response: Amendment
Application Number: 09/758,831
Attorney Docket Number: 150562.01

22. (original) A system as in claim 18, wherein the switching component is controllable to introduce errors in network communication data passing therethrough.

23. (original) A system as in claim 17, wherein the switching component is programmed for monitoring flows of network communication data from the network servers to the network clients.

24. (Currently Amended) A method of testing a plurality of network servers in a private network, comprising the steps of:

connecting the network servers to a plurality of network adapters; receiving network communication data from an external network;

directing the received network communication data to the network adapters for transmission to the respective network servers in the private network connected thereto;

selectively disabling the network adapters <u>using a test control component</u> to create failure of physical connections between the network adapters and the network servers in the private network connected thereto; <u>and</u>

communicating, using the test control component, to a server testing controller on the external network through a third network adapter separate from others of the plurality of network adapters.

25. (original) A method as in claim 24, further including the step of operating on the network communication data received from the external network to create a test condition other than a connection failure condition before sending the network communication data to the network servers through the network adapters.

Type of Response: Amendment Application Number: 09/758,831 Attorney Docket Number: 150562.01 Filing Date: January 11, 2001 26. (Currently Amended) A method as in claim 25, wherein the step of

operating includes selectively buffering network communication data passing

therethrough for a <u>preselected</u> delay period.

27. (original) A method as in claim 25, wherein the step of operating

includes selectively dropping network communication data passing therethrough.

28. (original) A method as in claim 25, wherein the step of operating

includes reordering network communication data passing therethrough.

29. (original) A method as in claim 25, wherein the step of operating

includes introducing errors to network communication data passing therethrough.

30. (Currently Amended) A method as in claim 24, further including the step

of monitoring flows of network communication data from the network servers to the

external network.[[.]]

31. (Currently Amended) A computer comprising:

a first set of network adaptors configured to connect the computer to a

plurality of clients through a first network;

a second set of network adaptors configured to connect the computer to a

plurality of servers through a second network;

Type of Response: Amendment

Application Number: 09/758,831

Attorney Docket Number: 150562.01

a switching module configured to identify incoming communication data from the clients received by the first set of network adaptors and to send the communication data to the servers through the second set of network adaptors; and

a testing module <u>including a third network adapter for connecting the testing</u> module to the external network to allow the testing module to communicate with a <u>server testing controller on the external network</u>, the testing module configured to create a failure of a physical connection to at least one of the servers by disabling the network adaptor corresponding to the at least one server in the second set of network adaptors;

wherein a fail-over mechanism associated with the plurality of servers is tested by the failure of the physical connection created by the testing module.

> Type of Response: Amendment Application Number: 09/758,831 Attorney Docket Number: 150562.01